

XLT-17

LIQUID LEAK DETECTOR



Fisher's NEW XLT-17 is a liquid leak detector that finds leaks in four easy steps: by electronically amplifying leak sounds, selectively filtering out noise, isolating the leak sound, and leading the operator to the source of the leak.

The XLT-17 leak detector is built to perform and priced to compete. The XLT-17 comes standard with Fisher's Multi-Sensor which has superior leak detection capabilities. The Multi-Sensor is in an extremely compact design with improved sensor electronics and better sensitivity to leaks.

In the Fisher tradition, the XLT-17 is affordable, tough, and simple to use while providing maximum performance. A two year limited warranty comes standard with the unit.

Features



- Detects and pinpoints liquid leaks in pipes
- 4 Frequency Filters: Low Pass, High Pass, Band Pass and All Pass
- Last setting memory feature
- Rugged membrane keypad
- Shielded sensor for reduced response to outside noise
- Improved headset for clearer sound response
- Automatic battery test - real time voltage level
Operates on two 9 volt batteries
- Compact control box that can be worn around the neck or over the shoulder with an attachable strap
- Heavy duty carrying case protects the XLT-17



200 W. Willmott Rd., Los Banos, CA 93635-5501

T 209.826.3292 F 209.826.0416 www.fisherlab.com info@fisherlab.com

Fisher Labs has been serving the demanding needs of the utility industry with innovative locating solutions - Since 1931. From pipe & cable locators, valve & box locators, sound & leak detectors to water level indicators, Find it... with Fisher!

XLT-17 specifications

FISHER M-SCOPE®

Specifications subject to change without notice.

Operating Frequency:

60 Hz – 6 kHz, Gain = 60 db

20 Hz – 60 Hz, Gain ≥ 55 dB

Filter Types and Frequency Ranges:

All Pass: 60 Hz to 6 kHz

Low Pass: Adjustable cut-off frequency from 150 Hz to 2.4 kHz

High Pass: Adjustable pass band frequency from 150 Hz to 2.4 kHz

Band Pass: Adjustable center frequency from 150 Hz to 2.4 kHz

Output Indications:

Audio High performance headphones (64 ohms)

Visual LCD bargraph and 2-digit numeric display

Grade of Protection Splash Proof

Battery Test Automatic, real time battery level indicator

Battery Quantity/Type Two, 9 Volt Alkaline

Battery Life 50 Hours (approximate)

Carrying Case Dimensions 21" x 6" x 14"

Weight: 10 lbs (unit in carrying case)

A ccessories

STANDARD EQUIPMENT:

Hard Carrying Case

Operation Manual

Control Unit

Head phones

Muti-Sensor

Carry Strap/Housing Bracket

Sound Rods



2-Year Warranty

Fisher warrants the XLT-17 to be free of defects in materials and workmanship when it is shipped from the factory. The terms of this warranty are fully explained in a warranty registration card that accompanies the instrument. Complete factory and field service facilities support the warranty.

*Warranty may vary outside the U.S. See your distributor for details.

Ordering Information

US & Canadian Customers Contact:

FISHER LABS

200 W. Willmott Rd., Los Banos, CA 93635-5501

T 209.826.3292 F 209.826.0416 info@fisherlab.com

www.fisherlab.com

All Other Countries Contact:

Fisher Export Department

280 State Street, Suite 202, North Haven, CT 06473 USA,

T 203.230.4130 F 203.248.8093

email: fisher@exportdept.com

